

Alcohol resistant, floor polish

Description

Alcohol resistant floor polish, based on a special polymer back bone with innovative wax technology. TASKI Jontec Resitol has superior resistance to alcohol and disinfectants versus conventional floor emulsions. This alcohol resistance combined with a light Eucalyptus fragrance makes it ideal to use in a healthcare environment where alcohol hand gels are commonly used. The protective film shows good resistance to wear and foot traffic.

Key properties

- Superior resistance to alcohol and disinfectant resistant versus conventional floor finishes
- Dries to give a hard durable polymer film
- Light Eucalyptus fragrance
- Good response to buffing

Benefits

- Ideal for use in a healthcare environment
- Good resistance to wear, even under heavy traffic levels
- Light fragrance and reduced polymer odours is appreciated by staff and patients in adjoining areas.
- Responds well to all common maintenance methods (ideal when maintained with Jontec Tensol).

Use instructions

- 1. Use appropriate TASKI Jontec Stripper to remove existing floor polish Ensure floors are clean and thoroughly dry.
- 2. Treat worn/ porous floors with a Diversey floor seal prior to application.
- 3. Apply using a mop or polish applicator in overlapping lanes of 1-1.5m. using a fig 8 motion.
- 4. Allow to dry completely (20-30 minutes) before applying additional coats.
- 5. Apply 2-3 coats.


Top stripping and recoating:

- 1. Use a Diversey floor top stripper to remove one coat of polish and pick up soiled solution with a scrubber drier or wet vacuum cleaner.
- 2. Allow to dry completely before applying additional coats.

Dosage:

Ready to use, no dilution required.





A.I.S.E.



Technical data

Appearance: Milky, white liquid

pH value (neat): 8.2 pH value (in use): 8.2

Relative density (20°C): 1.03 g/cm³

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature.

Only for professional users / specialists. Do not store or use at temperatures below 5°C.

Product compatibility

Do not mix with other products. Do not use outdoors or in areas liable to water contamination e.g. washrooms or kitchen areas.

Approvals

Slip resistance 0.5 minimum (ASTMD D 2047).

Available pack sizes

TASKI Jontec Resitol is available in 2x5L.